

Wessell, Nickel & Gross

Grand Piano Damper Action Order Form

Contact Information

Date _____ Country _____
Name _____ Zip / Postal _____
Address _____ Phone _____
City _____ Email _____
State/Province _____
Make & Model of Piano _____ Serial Number of Piano _____

Damper Action (Back Action)

Rails drilled and assembled

Yes No Total no. of dampers _____

Flange Rail

- Thin (Requires 72mm from belly rail to center of damper wire)
 Thick (Requires 86mm from belly rail to center of damper wire)

Under Levers

Spoon Length

- Short (Under lever center to spoon length of 73.6mm)
 Medium (Under lever center to spoon length of 76.6mm)
 Long (Under lever center to spoon length of 81.6mm)

Sostenuto Tab

- WNG Standard Top Flange (low sostenuto tab height)
 WNG Aftermarket Top Flange (high sostenuto tab height)

Leading (additional charge of \$50.00 for custom leading)

- Standard Leading (2 Leads [32], 1 Outside Lead [12], 1 Inside Lead [12], 0 Leads [12])
 Custom Leading (2 Leads ____, 1 Outside Lead ____, 1 Inside Lead ____, 0 Leads ____)

Damper Assist Springs (35 springs per kit)

No. of Damper Assist Spring Kits (35 springs per kit, \$18.00 per kit) _____
No. of notes to install with springs (installation charge of \$1 per note) _____

Damper Heads & Wires (additional charge)

- Yes No
 Ebony Satin Ebony Polish
No. of bass dampers _____

Sostenuto Rod Kit (additional charge of \$75.00)

- Include Sostenuto Rod Kit
 Assemble to customer specifications (additional charge of \$20.00 and scale stick required)

Comments / Special Requirements

Section for WNG Use Only

A _____ B _____ C _____ S/O# _____